

SN-IRC13/64FVD(II)


720P Hybrid Analogue Eyeball



Key features

- 1/4" Progressive Scan CMOS
- 3.6mm
- Full HD 720P
- Video Transmission 300m
- IR Up to 20m
- 2D DNR,dWDR,ICR
- Support AHD/TVI/CVI/CVBS Output
- IP66

Dimension



Accessories



SN-BK322A



SN-CBK629A

Specifications

CAMERA	
Image Sensor	1/4" CMOS
Signal System	PAL/NTSC
Min. illumination	Color:0.05Lux@(F1.2,AGC ON) ; B/W:0Lux@(IR LED ON)
S/N Ratio	≥50dB
Day & Night	ICR
Shutter Speed	PAL:1/50-1/50000, NTSC:1/60-1/60000
Wide Dynamic Range	dWDR
Digital Noise Reduction	2D
Lens	3.6mm
FOV	85°
IR LED	18pcs
IR Wavelength	850nm
IR Range	Up to 20m
OSD Joystick	Optional
Up the Coax	Support
IMAGE	
Effective Resolution	1280x720
Frame	PAL:25fps ,NTSC:30fps
Mirror	N/A
Defog	N/A
HLC	N/A
Privacy Masking	N/A
Motion Detection	N/A
VIDEO OUTPUT	
Max Distance	75-5 300m
Video Output	AHD/TVI/CVI/CVBS
GENERAL	
Power Supply	DC12V±10%
Power Consumption	3.5W(Max)
Operating Temperature	-10°C ~ 55°C (14°F ~ 131°F)
Operating Humidity	0% - 85% RH
Ingress Protection	IP66
Approvals	CE / FCC
Material	Aluminium Alloy
Product Dimensions	Φ94×84mm
Product Weight	360g